



GT -10 touch Tab 10-Inch Wall & Table Mount PoE Touch Panel

GT -10 touch Tab is a new powerful, 10-inch, IPS, multi-touch, touch panel with 1920×1200 resolution. Elegantly designed for decorative room integration, this portable touch panel can be deployed either on a tabletop or wall. GT -10 touch Tab, with the latest Android 11, supports wired PoE (Power over Ethernet) and advanced Wi-Fi connectivity options. The touch panel has a built-in speaker and camera and comes either with a tabletop or a wall mount. The touch panel is easy to assemble, using elegant wiring, secured mounting, reliable operation and flexible deployment. GT -10 touch Tab is a touch panel that is ideal for any 24/7 supported commercial AV or control application and features a user-friendly, fully customizable graphical user interface configured by software

Feature:-

- **Elegant Design** - Smooth integration with room furniture design, either on table or wall, with flexible panel cabling and locking design options
- **Superior User Experience** - IPS 1920×1200 hi-resolution screen with ±80° horizontal and vertical wide viewing angles, ambient light sensor, proximity sensor, with advanced multi-touch points and 2-finger gesture capabilities
- **Powerful Processing** - i.MX8M Plus Quad Core A53, 4GB RAM, 32GB ROM processing performance, smoothly running complicated media and graphics-rich applications, such as H.265 video, audio streams encoding and decoding, and seamless hi-resolution 5Mp FF camera operation
- **Flexible Services** - Latest Android 11 operating system
- **Easy Installation** - Powering and connectivity via a single Ethernet cable
- **Flexible Mounting** - Including table and wall mounts
- **Optional Connectivity** - Simple wireless Bluetooth 5 as well as connection to USB peripheral devices for either table or wall-mount installations, using the included USB cable
- **Reliable Networking** - Seamless switching between wired and wireless 802.11ac connectivity
- **Versatile Powering Options** - PoE and power adapter (sold separately)
- **Auto Sensing** - Optimized performance and operation according to automatically detected LAN speed
- **Firmware Update** - Define automatic updates on a predefined time of the day or update manually using USB port
- **Secured Operation** - Highly secured operation of applications using password protection, hidden control buttons and more. Red LED alert when camera is active
- **Secured Deployment** - Flexible locking options to prevent unwanted panel mount removal, elegantly designed to remain out of site

TECHNICAL SPECIFICATIONS

Ports	<p>1 Ethernet: On an RJ-45 connector with PoE 802.3at</p> <p>1 USB: On a USB type C (ADB) connector</p> <p>1 USB: On a USB Type A connector</p>
General	<p>CPU Performance: ARM Quad-core Cortex-A53 up to 1.8GHz (64 bit)</p> <p>System Memory: 4GB LPDDR4</p> <p>Internal Storage Memory: 32GB eMMC</p> <p>Wireless Communication: Wi-Fi 6, 802.11 a/b/g/n/ax/ax+BT 5.0</p> <p>Ethernet: 10/100/1000 Mbps LAN</p> <p>Display Screen: Multi-touch (PCAP)</p> <p>Display Size 10.1" (16:9 diagonal), 1920 RGB (H) x 1200(V) pixels</p> <p>VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA mount</p> <p>Contrast Ratio: 350cd/m2 brightness, 1000:1</p> <p>Back-light: LED Side-light type (GT-2010WM only)</p>
Audio	<p>Speaker Unit: built-in, 2x 1W</p> <p>Microphone: 2, Built-in</p> <p>Audio Codecs: MPEG/OGG/AAC</p>
Video	<p>Camera: 5Mp FF</p> <p>Video Format: H.264 / H.265,VC-1, MPEG-4, VP9/VP8</p> <p>Image Codecs: JPEG/BMP/GIF/PNG</p>
Power	<p>PoE: Power over Ethernet 802.3af(/at)</p> <p>Source: 12V/2A DC adapter (optional)</p>
User Interface	<p>Controls: Volume, menu, and power buttons</p> <p>Indicators: GT-201WM has LED sidebars to indicate room status (requires 3rd party integration)</p>
Accessories	<p>Included: 2 LED side bars on GT-2010WM, table mount for GT-2010 or on-wall mounting bracket & panel mounting bracket for GT-2010WM, installation screws</p>
Environmental Conditions	<p>Operating Temperature & Humidity: 0° to +40°C (32° to 104°F), 5% to 85%</p> <p>Storage Temperature & Humidity: -20° to +60°C (-4° to 140°F), 5% to 90%</p>
PHYSICAL	<p>Product Dimensions: 24.2x1.85x17.3 (9.5" x 0.73" x 6.8") W,D,H</p> <p>Package Dimensions: 30.9cm x 24.2cm x 17.5cm (12.2" x 9.5" x 6.9") W, D, H</p> <p>Product Weight: 0.56kg (1.2lbs) approx</p> <p>GT-2010 Package Weight: 1.4kg (3.1lbs) approx</p> <p>GT-2010WM Package Weight: 1.2kg (2.6lbs) approx</p>
Product Dimensions	24.20cm x 1.85cm x 17.30cm (9.53" x 0.73" x 6.81") W, D, H
Product Weight	0.6kg (1.2lbs) approx
Shipping Dimensions	41.80cm x 34.40cm x 34.40cm (16.46" x 13.54" x 13.54") W, D, H
Shipping Weight	1.2kg (2.6lbs) approx

CONFIGURATIONS

GT-2010	10-Inch Table Mount PoE Touch Panel
GT-2010WM	10-Inch Wall Mount PoE Touch Panel

