



GT-N02008-KNA

Garantir Network Video Recorder is designed for use within a surveillance system along with Number Plate Recognition (ANPR) and performs recordings and playbacks pictures from network cameras in the system. It is an 8-channel network video recorder (NVR) for SMB/Enterprise & ANPR applications. It provides uninterrupted recording also in full frame rate 4K resolution for all channels. It is possible to perform the settings/configuration or operate the NVR using a web browser installed on a PC connected to a network and live videos can be viewed on major mobile devices through its web browser and recorded video can be played back from remote site by a PC.

Garantir NVR is compatible with most major brand cameras and its ability to automatically search and find the available cameras on the network can greatly reduce the user's effort when configuring the system.

KEY FEATURES

- Compact 1U Rack mountable Housing Design
- Support up to 8MP (4K) IP camera Input IP Camera Input
- Built in 2 Hard disk bays with SATA interfaces.
- High Quality Live/ Playback Video.
- Automatic Number Plate Recognition (ANPR) Support.
- Built-in HDMI with 4K Resolution
- Supports Digital Zoom
- Supports ONVIF and RTSP Protocols
- Gigabit Network Interfaces
- Support ANR Function
- Two-way Audio
- Backup Recorded Video to USB HDD
- Support Advanced Video analytics features.
- Support Smart recording, Smart Search and Smart Playback

8CH ANPR EMBEDDED NETWORK VIDEO RECORDER

Parameters	Specifications
Application	Indoor Rack Mountable
Main Processor	Quad Core Embedded Processor
Operating System	Embedded Linux
Video & Audio	
IP Video Input	8-Channel
Throughput	80Mbps (Incoming) / 48Mbps (Outgoing)
HDMI 1 Output	4K (3840×2160), 1920×1080, 1280×1024, 1280×720, 1024×768
VGA 1 Output	1920×1080, 1280×1024, 1280×720, 1024×768
Audio Output	1-ch, RCA
Two-way Audio	1-ch (using the input RCA)
Split Screen Matrix	Multiple options with 1/4/8
OSD Support	Title/ Week/ Date/ Time/ Text (option of different colours & sizes)

Decoding & Monitoring	
Decoding Format	Smart H.265/ H.265/ Smart H.264/ H.264
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/D1/VGA/CIF/QCIF
Synchronous Playback	8-ch at 720P
Decoding Capability	1-ch@8 MP/2-ch@6 MP/2-ch@5 MP/3-ch@4 MP/6-ch@1080p/8-ch@720p
Audio Compression	G.711ulaw/G.711alaw & AAC
Video Bit Rate	32 kbps to 16 Mbps per channel with CBR & VBR support
Audio Bit Rate	Up to 256 kbps
Recording Type	Manual, Continuous (24×7), Schedule, Alarm & Alert based, ANR (file size can be configure based on file size or recording time)
Pre/Post Record	Supported, Pre Record time: 30 sec, Post Record time: 3600 sec
Live View Options	Stream selection, Split screen, Alarm, Snapshot, Record, Mic, Audio Volume adjustment, Full screen, Digital zoom etc.
Playback Options	Play, Pause, Stop, Fast/Slow play, Full screen, Backup, Snapshot, Clip management, Split screen etc.
Backup Mode	USB & Network
Export Picture	JPG format
Export Video	MP4 & AVI format
Network, Interface & Storage	
Protocols	IPv4, IPv6, ICMP, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, NTP, SNTP, SMTP, SNMP, UPnP, NFS
Integration	ONVIF Profile (S, G & T), SDK, API
Network	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
USB Interface	2 x USB 2.0
Alarm In/Out	4/1
SATA	2 SATA Interfaces
Hard Disk	Up to 10 TB capacity per HDD slot
Smart Functions	
Analytics	Configurable special camera with smart functions, such as VCA detection like Motion detection, Perimeter, Line crossing (single/ dual), Loitering, Running, Parking, Object Left, Missing Object, Face detection, People count, Crowd estimation, Video abnormal, Audio abnormal, Auto tracking, License Plate Recognition, Heatmap
Alarm types	Input alarm, Output alarm, I/O alarm error, access denied, IP & MAC conflict, Network disconnected, Hard disk full & error (r/w, overload & SMART), No hard disk, Abnormal recording & temperature, Array error, Hot spare error, Motion detection, Tampering, Analytics detection, Video loss

General	
User Authentication	Up to 32 users
Firmware Upgrade	Through USB & Web browser
Power Supply	12V DC
Power Consumption	≤5W (without HDD)
Working Environment	-10°C to 55°C
Humidity	10% ~ 90% Relative Humidity
Chassis	Max 1U
Dimensions	51.8 × 317.6 × 380 mm
Net Weight	1.9 Kg

Ordering Information:

GT-N02008-KNA

8 Channels Network Video Recorder with 2 Hard Disk Slot, ANPR, 4K Cameras, HDMI, Analytics and ONVIF support.

