



GT-USBC-MPA-50
USB-C Multiport Adapter

The **GT-USBC-MPA-50** is a compact USB-C hub multiport adapter that enhances connectivity by offering HDMI and DisplayPort outputs, three USB 3.2 Gen 1 ports, an Ethernet port, and an audio/microphone port. It also includes a USB-C charging pass-through, making it ideal for personal workstations and small meeting spaces.

Features:-

- HDMI and DisplayPort Video Outputs
- USB 5G Speed Connection
- Ethernet 1Gbps Support
- 3.5 mm Headset Jack

Category	GT-USBC-MPA-50 Specification
Inputs	1 USB -C: On a USB Type - C female connector
Outputs	1 HDMI: On a female HDMI connector
	1 DisplayPort: On a female DisplayPort connector
	1 USB 3.2 Gen 1: On a female USB type - A connector (5V/1.5A)
	1 USB 3.2 Gen 1: On a female USB type - A connector (5V/0.9A)
	1 USB 3.2 Gen 1: On female USB type - C connector (5V/0.9A)
	1 Ethernet: On an RJ-45 connector (10/100/1000)
	1 3.5 mm Headset Jack: for audio and Microphone
	1 USB: On a female USB type -C connector for charging (100W max)
	1 USB: On a female USB type- C connector for host connection
	Video
Windows MST Mode Max. Resolution: 3840×2160P@30Hz (two displays)	
MAC OS SST Mode Max Resolution: 3840×2160P@60Hz (single/dual)	
Extended Ethernet	Max Data Rate: 1000M (Gigabit)/100M/10M
	Includes: Wake-on-LAN (WoL), single Mac address, PXE boot
General	USB 3.0 Data Transmission Speed: Up to 5.0Gbps
Product Dimensions	16.4cm x 6.4cm x 1.9cm (6.5" x 2.5" x 0.7") W, D, H
USB 3.2 Gen 1 Data Transmission Speed	Up to 5.0Gbps
Power Delivery	100W
USB Charging	BC1.2 (5V 1.5A)
USB Limited Current when	1.9A

Connected to Power	
USB Limited Current when Not Connected to Power	1A

