



**GT Speaker**  
2-Way Speaker

The **GT Speaker** is a high-performance 2-way closed-back ceiling speaker engineered for optimal sound quality. It includes a multi-tap power transformer that lets users choose between 8Ω (transformer bypass) and 70V/100V power settings, making it well-suited for diverse array installations.

Features:-

- Type
- Woofer
- Tweeter
- Impedance
- Power Handling
- Transformer Taps

Category	GT Speaker Specification
Description	2-way closed-back ceiling speakers
Frequency Response	80Hz to 20kHz @ -10dB, 95Hz to 20kHz @ ±3dB
Woofer	6.5" (165mm) polypropylene with rubber surround
Tweeter	0.5" (13mm) Mylar dome
Impedance	8Ω (transformer tap in off position)
Transformer Taps	70V- 3.7W/7.5W/15W/30W/Off (Lo-Z), 100V- 7.5W/15W/30W/Off (Lo-Z)
Sensitivity	87dB SPL, 1W @ 1m
Max SPL	Continuous: 100.7dB, Peak: 103.7dB
Power Handling	30W RMS, 80W continuous program
Crossover Frequency	9.2kHz
Coverage Angle	101°
Directivity Factor (Q)	7.5 averaged 1kHz to 10kHz
Directivity Index (DI)	8.6dB averaged 1kHz to 10kHz
Input Connector	Terminal block
Materials	ABS bezel, aluminum grill, metal back can

